

ᅏ

玉 Z

0

HDTV

FULLY COLOR CORRECTED AND FILTERED LENSES EYE-Q" AUTO-CONVERGENCE RS-232 CONTROLLABLE



DTV-992 ULTRA



DTV-873











he DTV-992 ULTRA has all the features necessary for the true home theater experience. With its true 8-inch CRTs, fully color-corrected and filtered lenses, and accurate 25-point zone convergence system, this projector will precisely reproduce video from any source. Its scan rate capabilities and large CRTs make it the perfect choice for use with any High-Definition format, as well as any type of processor. Finally, this unit comes equipped with the Eye-Q $^{\scriptscriptstyle\mathsf{TM}}$ auto-convergence system for easy touch-ups.

FEATURES

- 25 point zone convergence
- 230 ANSI lumens
- Color corrected and filtered HD-8 lenses
- \bullet Eye-QTM: The intelligent way to converge
- Impressive gamma correction

- RS232 controllable
- Multiple Aspect Ratios
- 110 KHz Horizontal scan rate
- 120 MHz Bandwidth
- Convergence on green for accurate linearity

SPECIFICATIONS

Scan Frequency: Horizontal: 15-110 KHz

Vertical: 37-200 Hz

Optical Resolution: 10 line pairs/mm

Video Standards: NTSC, PAL, SECAM, NTSC 4.43

Bandwidth: 75 MHz (120 MHz 992 Ultra)

CRTs: 8" High performance with Electromagnetic focus

Lenses: Fully color corrected and filtered

HD-8 lenses

Inputs: Component/RGB

Color Balance: 3200K, 5400K, 6500K, 9300K,

Custom

Light Output: 1250 lumens/230 ANSI lumens

Convergence Memories: 32

Picture Size: 5–20 ft. wide

Throw Distance: 1.33 x width (widescreens)

1.40 x width (4:3 screens)

Configurations: Front or rear, floor, or ceiling

mount

Aspect Ratio: Anamorphic, widescreen, 4:3

Contrast Ratio: 100:1

Convergence: Dynamic geometry, 25 point zone

Power Requirements: 115 VAC, 50/60 Hz

Power Consumption: 500W

Cabinet Dimensions: Width: 23.25 in./590.55 mm

Depth: 43 in./1092.20 mm Height: 14.25 in./361.95 mm Weight: 156 lbs./70.76 mm

Safety Regulations: Complies with: FCC Class B, CE,

C-Tick

Storage: $10-122^{\circ} \text{ F } (-12-50^{\circ} \text{C})$ Operating Environment: $32-104^{\circ} \text{ F } (0-40^{\circ} \text{C})$

Humidity: 0–90%, non-condensing

Call factory for more specific information on export specifications.

Specifications are subject to change without notice.



Runco International® 2463 Tripaldi Way, Hayward CA 94545 Tel: 510-293-9154 • Fax: 510-293-0201

www.runco.com